

The Fun Quilter utilizes the same sewing apparatus as our world famous Pro and NV commercial longarm quilting machines.



Intellistitch Equalizer



Round Foot For Ruler Guides


- 17", 20" or 23" throat depth, with 8" of inside height.
- Weighs only 34 to 39 pounds depending on model.
- Front handles for custom quilting.
- Rear handles and pointer for pantograph quilting.
- Select stitch regulator or standard speed mode with sewing speeds up to 2500 stitches per minute.
- Round hopping foot for using rulers and templates.
- Convenient front and rear hand wheels.
- Fluorescent light above the needle.
- Light weight machine body with walls constructed of strong solid aluminum.
- Complete systems include frame and accessories.
- Custom built, individually, by skilled craftsmen at the Nolting manufacturing facility in Hiawatha, Iowa.

LOUTING®



NEEDLE BUTTON

The Needle up/down button is great for basting, bringing up bobbin thread or locking stitches at the beginning or end of your design.



LOW MAINTENANCE

Only 1 drop of oil every 8 hours of continuous use. No oil reservoirs or complex places to access.

THREAD PATH

Obvious thread path and tension device help you achieve your desired stitch quality.

12" FLORESCENT LIGHT

Light the work area perfectly. Switch out and insert a black light when needed.

HOPPING FOOT ASSEMBLY

Just right for rulers and guides.

ASK ABOUT OUR COMPLETE PACKAGES AND OPTIONS

Complete packages include machine, frame, needles, bobbins, bobbin winder, oil, patterns, clamps, leaders, product manuals, and 5-year warranty. Additionally, Nolting offers exceptional services such as delivery, package installations, and superior professional training. Fun Quilters are designed to work on most frames. Ask your Nolting representative if we have a size to fit your frame.



Bobbin Winder



Popular "L" bobbin



Nolting Commercial Steel Frame

NOLTING AREA DEALER:

1105 Hawkeye Dr. • Hiawatha, Iowa 52233

Phone: (319) 378-0999 Email: nolting@nolting.com

www.nolting.com

